



Heavy-Duty Antifreeze

Extended-Life Coolant

50/50 Pre-Diluted

- Formulated with ethylene glycol, deionized (purified) water and performance additives
- Maximum protection against freezing, boil-over, and corrosion
- For use in heavy-duty diesel engines, but suitable for use in most conventional automotive and diesel engines

EXCEEDS PERFORMANCE REQUIREMENTS:

ASTM D-3306	ASTM D-4340	ASTM D-4985	
ASTM D-6210	Cummins 14603	Caterpillar	
Chrysler MS7170 Sec. A and B 1-4		GM 1825M	GM 1899M
Ford ESE-M97B44-A Sec. 3.1.1 and 3.1.2		Detroit Diesel 7SE298	
Freightliner 48-22880	John Deere H24A1, H24C1	Mack Truck	MTU
Navistar B1	TMC RP 329	Volvo-GM Heavy Truck	

SPECIFICATIONS:

<u>PARAMETER</u>	<u>TYPICAL</u>
Appearance	Red Liquid
Specific Gravity	1.06
Freezing point, °F	-34
pH	8.3
Reserve Alkalinity	6
Silicates, wt%	<0.05

PRODUCT CODES:

- Bulk - MXHDAF
- 1000L Tote - MXHDAFT
- 55G Drum - MXHDAFD
- 5G Pail - MXHDAFP
- 6/1 Gallon Case - MXHDAFG

