



Premium Hydraulic Oils

ISO 32, ISO 46, ISO 68

Anti-Wear (AW)

- Formulated with Group II, High-Viscosity Index Base Oils
- Excellent Demulsability
- Superior protection against wear
- Superior protection against rust and oxidation
- Multipurpose oil for wide array of applications
- Premium performance anti-wear additive package

EXCEEDS PERFORMANCE REQUIREMENTS:

- Dennison HF-0, HF-1, HF-2
- Cincinnati Machine P-68, P-69, P-70
- Eaton Vickers M-2950-S, I-286-S
- General Motors LS-2, LH-03, LH-04, LH-06
- DIN 515524 Part 2
- JCMAS HK
- US Steel 127

SPECIFICATIONS:

ISO Viscosity Grade	ISO 32	ISO 46	ISO 68
Density g/cm ³	0.871	0.875	0.879
Lbs/Gal	7.269	7.302	7.336
Appearance	Slight Yellow Liquid, Free and Clear		
Viscosity cSt @ 40°C	31.9	46.5	68.2
Viscosity cSt @ 100°C	5.43	6.97	9.11
Viscosity Index	103	105	108
Flash Point, °C	204	206	210
Pour Point, °C	-27	-27	-25

PRODUCT CODES:

ISO VG	ISO 32	ISO 46	ISO 68
Bulk	MX32AW	MX46AW	MX68AW
1000L Tote	MX32AWT	MX46AWT	MX68AWT
55G Drum	MX32AWD	MX46AWD	MX68AWD
5G Pail	MX32AWP	MX46AWP	MX68AWP

