



# Synthetic Blend Heavy-Duty Motor Oil

## 15W-40

API CJ-4/SN

- Premium Blend of Group II and Synthetic Base Oils
- Premium HD Performance Additive Package
- Superior protection against wear, corrosion, and oxidation
- Prevents sludge or carbon deposits
- Enhances engine performance by easing cold starts
- Eliminates Viscosity Breakdown

### EXCEEDS PERFORMANCE REQUIREMENTS:

API CJ-4	API CI-4	API CI-4 PLUS	API CH-4	API CF-4	API CF-2	API CF
API SN	API SM	API SL	API SJ	API SH	API SG	API SF
MB 228.31	MB 228.1	MB 229.1	Volvo VDS-4		Volvo VDS-2	
Renault RLD-3		Renault Truck RD/RD-2		MTU Type 1		MAN 271
CAT ECF-3		CAT ECF-2	CAT ECF-1-a		CUMMINS CES 20076	
Cummins CES 20081		Mack EO-O Premium Plus 07		Mack EO-M Plus		

### SPECIFICATIONS:

SAE VISCOSITY	15W-40
Density g/cm <sup>3</sup>	0.881
Lbs/Gal	7.352
Appearance	Light Amber Liquid, Free and Clear
Viscosity cSt @ 40°C	118.15
Viscosity cSt @ 100°C	14.5
Viscosity Index	125
Flash Point, °C	210
Pour Point, °C	-34

### PRODUCT CODES:

Bulk	MX154J
1000L Tote	MX154JT
55G Drum	MX154JD
5G Pail	MX154JP

